

TABLET COMPUTER

DT10

USER'S GUIDE

Notice

Copyright© 2015, MilDef Crete Inc. All rights reserved.

No part of this publication may be reproduced and modified without the written permission of MilDef Crete Inc.

MilDef Crete Inc. reserves the right to make changes in the products or the product specifications without any prior notice. Customers are advised to contact MilDef Crete Inc. for updated product information.

MilDef Crete Inc. makes no representations or warranties, either expressed or implied, with respect to the contents hereof and specifically disclaims any warranties for the correctness of this book, nor any license grant of MilDef Crete Inc.'s patents or intellectual properties. MilDef Crete Inc. assumes no liability for customer's loss or damage caused by using this document.

Trademarks

Trademark Acknowledgments

Intel® is a registered trademark of Intel Corp.

All product and company names are trademarks or registered trademarks of their respective holders.

Revision History:

Revision	Date	Changes	Author
1.0.0	2015/05/20	Official Release	Pablo Tseng

Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Regulatory Information/Disclaimers

Installation and use of this computer must be in strict accordance with the instructions included in the user documentation provided with the product. Any changes or modifications (including the antennas) made to this device that are not expressly approved by the manufacturer may void the user's authority to operate the equipment.

The manufacturer is not responsible for any radio or television interference caused by unauthorized modification of this device, or the substitution of the connecting cables and equipment other than manufacturer specified. It is the responsibility of the user to correct any interference caused by such unauthorized modification, substitution or attachment. Manufacturer and its authorized resellers or distributors will assume no liability for any damage or violation of government regulations arising from failing to comply with these guidelines.

FCC (Federal Communications Commission) Statement

This equipment has been tested and found to comply with the limits for a Class-B digital device pursuant part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses, and radiates radio frequency energy. If not being installed and used in accordance with the instructions, it may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Re-orient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.



FCC Caution:

To assure continued compliance, any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. (Example - use only shielded interface cables when connecting to computer or peripheral devices).

CE

Products with the CE Marking comply with both the EMC Directive (2004/108/EC) and the Low Voltage Directive (2006/95/EC) issued by the Commission of the European Community.

Compliance with these directives implies conformity to the following European Norms:

EN55022 CISPR 22 Radio Frequency Interference

EN55024 EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11, EN61000-3-2, EN61000-3-3, Generic Immunity Standard

LVD EN 60950-1: 2006+ A11: 2009+ A1: 2010+ A12: 2011+ A2: 2013
IEC 60950-1: 2005+AM1:2009

R&TTE (CE) Manual Regulatory Requirement

WLAN - IEEE 802.11a/b/g/n

802.11a/b/g/n Restrictions:

European standards dictate maximum radiated transmit power of 100mW EIRP and frequency range 2.400-2.4835 GHz. In France, the equipment must be restricted to the 2.4465-2.4835 GHz frequency range and must be restricted to indoor use.

CE Declaration of Conformity



It is confirmed to comply with the requirements set out in the Council Directive on the approximation of the laws of the member states relating to Electromagnetic Compatibility (2004/108/EC), Low-voltage Directive (2006/95/EC), the Amendment Directive (93/68/EEC), and the procedures given in European Council Directive (99/5/EC and 2004/108/EC).

The equipment was passed, and the equipment test was performed according to the following European standards:

EN 300 328 V1.8.1 (2012)

EN 301 893 V1.7.1 (2012)

EN 301 489-1 V1.9.2 (2011)

EN 301 489-3 V1.6.1 (2013)

EN 301 489-17 V2.2.1 (2012)

EN62311 2008

EN300440-1 V1.6.1 2010

EN300440-2 V1.4.1 2010

UL, TÜV

AC Adapter (TÜV includes **LVD EN60950**)

Power Conservation

This tablet computer consumes less power compared to conventional consumer computers. The power consumption may be further reduced by properly configuring the Power Management Setup.

It is recommended that the power saving features be enabled even when not running on battery power. Power Management features can conserve power without degrading system performance.

Power Safety

There are specific power requirements for your tablet computer:

- Only use an approved AC adapter designed for this tablet computer.
- There is a 3-prong grounded plug for the AC adapter. The 3rd prong is an important mechanism for ensuring product safety. Please do not neglect the importance of this mechanism. If you are unable to access a compatible outlet, please hire a qualified electrician to install a compatible outlet for you.
- When unplugging the AC power cord, please make sure to disconnect the cord by pulling from the plug head instead of pulling from the wire to prevent wire damage.
- Make sure the power outlet and any other extension cord(s) you use can support the total current load of all the connected devices.
- Before cleaning the tablet computer, please make sure it is disconnected from any external power source.



Warning

Before any upgrade procedures, make sure the power is turned off, and all the cables are disconnected (including telephone lines). Also, it is advisable to remove your battery to prevent your tablet computer from accidentally turning on.

Battery Precautions

- Only use batteries designed for this tablet computer. Using incompatible battery types may cause explosion, leakage or damage to the computer.
- Do not remove the battery from the computer while the computer is powered on.
- Do not continuously use a battery that has been dropped, or that appears damaged (e.g. bent or twisted) in any way. Even if the computer is able to continuously work with a damaged battery, the circuit damage may occur and possibly cause fire.
- Always use the charger designed for this computer to recharge the battery. Incorrect recharging may cause the battery to explode.
- Do not try to service a battery by yourself. For battery service or replacement, please contact your service representatives.
- Please dispose of damaged battery promptly and carefully. Explosion or leakage may occur, if the battery is exposed to fire, improperly handled or discarded.



Battery Disposal & Caution

The product that you have purchased contains a rechargeable battery. The battery is recyclable. At the end of its service life, under various state and local laws, it may be illegal to dispose of this battery into the municipal waste stream. Check with your local solid waste officials for details in your area for recycling options or proper disposal. Danger of explosion may possibly occur, if the battery is incorrectly replaced. Replace only with the same or the equivalent battery recommended by the manufacturer. Discard the used battery according to the manufacturer's instructions.

Environmental Information, Material Safety & Recycling

All materials used in the manufacturing of this equipment are recyclable or environmentally friendly. Please recycle the packing materials in accordance with local regulations at the end of the product's service life.

Notice:

- The equipment may contain insignificant amount of hazardous substances for health and environment below control level.
- To avoid spreading such substances into the eco system and to minimize the pressure on the natural environment, you are encouraged to reuse or recycle most of the materials in a safe way after the product's service life.
- For more information on collection, reuse and recycle of materials, please consult local or regional waste administrations for more information. You can also contact your dealer for more information on the environmental details of the equipment.
- The symbol of the crossed out wheeled bin indicates that the product (electrical and electronic equipment) should not be placed in municipal waste. Please check local regulations for disposal of electronic products.



TABLE OF CONTENTS

CHAPTER 1 - GETTING STARTED.....	1
UNPACKING	1
WORKPLACE	2
ENVIRONMENTAL RATINGS	2
RUGGEDNESS	3
APPEARANCE OVERVIEW	4
READY FOR USE.....	9
 CHAPTER2 - OPERATING INFORMATION.....	 11
START USING YOUR TABLET COMPUTER.....	11
STOP USING YOUR TABLET COMPUTER	12
WORKING WITH POWER BUTTON (HEATER KIT)	13
INSTALLING OPERATING SYSTEM	14
USING INDICATORS AND KEYBOARD	14
USING HARD DISK DRIVE (HDD) / SOLID STATE DRIVE (SSD).....	17
USING EXPRESSCARD	18
USING SD CARDS	19
INTEL® RAPID START TECHNOLOGY	20
USING THE TOUCH SCREEN	21
OPERATING WIRELESS DEVICES.....	23
USING INVISIBLE MODE (OPTION)	31
USING DOCKLIGHT DL10 (OPTION)	32
 CHAPTER3- MANAGING POWER	 33
AC ADAPTER	33
BATTERY	34
ACPI SUPPORT	36
USB FAST CHARGING	37
 CHAPTER 4 - BIOS SETUP.....	 38
MAIN MENU	38
ADVANCED MENU	39
TRUSTED COMPUTING SUB-MENU	41
SATA CONFIGURATION SUB-MENU	42
SATA CONFIGURATION SUB-MENU SELECTIONS	42
INTEL (R) RAPID START TECHNOLOGY SUB-MENU	43
USB CONFIGURATION SUB-MENU	44
USB CONFIGURATION SUB-MENU SELECTIONS	44
IT8783F SUPER IO CONFIGURATION SUB-MENU.....	45
RF DEVICE CONTROL CONFIGURATION SUB-MENU.....	46
EC THERMAL CONTROL SUB-MENU.....	47
CHIPSET MENU	48

CHIPSET MENU SELECTIONS	48
PCH-IO CONFIGURATION SUB-MENU	48
BOOT MENU	50
BOOT MENU SELECTIONS	50
SECURITY MENU	51
SAVE & EXIT MENU	52

CHAPTER 5 – DRIVERS AND APPLICATIONS 53

CHIPSET	53
VGA	54
AUDIO	54
INTEL ME	55
INTEL RAPID STORAGE TECHNOLOGY	55
WIRELESS POWER MANAGER.....	56
TOUCH SCREEN	56
USB3.0	57
RICOH SD CONTROLLER.....	57
TURBO BOOST MONITOR	58
GIGABIT LAN	58
2ND GIGABIT LAN (OPTION)	59
WiFi (OPTION)	60
BLUETOOTH (OPTION)	60
GPS (OPTION).....	61
WWAN (OPTION)	62
TPM (OPTION).....	63

CHAPTER 6 – SPECIFICATIONS..... 64

PLATFORM.....	64
CPU	64
PCH	64
MEMORY	64
TOUCH SCREEN	64
HARD DISK DRIVE (HDD)/ SOLID STATE DRIVE (SSD).....	64
KEYBOARD	64
AUDIO	65
I/O PORTS.....	65
DIMENSIONS AND WEIGHT.....	66
POWER.....	66
ENVIRONMENTAL, SAFETY & EMC.....	67
OPERATING & STORAGE TEMPERATURE.....	67
MATERIALS AND RECYCLING	67

CHAPTER 7 – OPTIONAL DEVICES 68

COMMUNICATION.....	68
MEMORY CARD	68

2ND BATTERY68

SECURITY68

DOCKLIGHT DL1069

MULTI-BATTERY CHARGER DR69

EXTERNAL USB KEYBOARD70

MINI KEYBOARD KBD71

CHAPTER 8 – MAINTENANCE AND SERVICE..... 72

CLEANING72

TROUBLESHOOTING72


RMA SERVICE73

Chapter 1 - Getting Started

Unpacking

The following components come with your computer. If anything is missing or damaged, please notify the dealer immediately.

- Computer unit
- AC Adapter
- AC Power Cord
- Utility DVD
- Quick Guide
- Carrying Bag



Workplace

A clean and moisture-free environment is preferred. Make room for air circulation. Remember to avoid areas from:

- Sudden or extreme changes in temperature.
- Extreme heat.
- Strong electromagnetic fields (Near television set, motor rotation area, etc.).
- Dust or high humidity.

If this tablet computer is required to work in a hostile environment, please maintain your tablet computer regularly by cleaning dust, water, and etc. to keep it in an optimal operating condition.

Environmental Ratings

Operating Temperature: I: 0~40 °C (32 ~ 104 °F)

M: -20 ~ 50 °C (-4 ~ 122 °F)

Opt.: -30 ~ 50 °C (-22 ~ 122 °F)

Storage Temperature: -40 ~ 70°C (-40 ~ 158°F)

Humidity: Operating/Storage: 5~95% (non-condensing)

Altitude: Operating/Storage: 4572 /12,180 meters (15,000/ 40,000 feet)

Ruggedness

The computer is designed with rugged features such as vibration, shock, dust, and rain/water protection. However, it is still necessary to provide appropriate protection while operating in harsh environments.

NEVER immerse the computer in water. Doing so may cause permanent damages. Drop may cause parts break or permanent damages.

The D-sub connector cap is for dust and shock protection only. The connector itself is sealed internally. Other I/O ports and devices must have caps tightly closed or cable inlets sealed while exposed to water or dust.


All connectors will corrode if exposed to water or moisture. Corrosion is accelerated if the power is ON. Please take proper measures in cable connection to avoid water entering into connectors.

The DC jack and cables are sealed and may be operated with water splashing while attached. All port covers should be in place when no cable is attached.

Appearance Overview


Note:

- The following illustrations show the tablet mounted on certain optional devices, which may not appear on your devices.

Front


1. Power Button
2. LED Indicators
3. Application Keys & Input Lock Key (Please refer to “Using Indicators and Keyboard” for more details)
4. Touch Screen
5. Keyboard

Rear



1. Secondary battery connector

Left




1. Battery
2. GLAN RJ45
3. USB 2.0 x 1 (Top)
USB 2.0 with Fast Charger x 1 (Bottom)
4. Multi Bay:
 - ExpressCard (Top)
 - SIM Card + SD Card (Bottom)

Note:

- *SIM Card slot function requires optional WWAN module installed in your tablet computer.*


Right




1. DC jack (2-pin for I model, 3-pin for M model)
2. Serial port DB9 (COM1, Default: RS232)

Note:

- The External COM1 port default is RS232, and can be selected by BIOS (RS232/RS422/RS485). Please refer to [IT 8783F Super IO Configuration Sub-Menu](#) in BIOS section.

Top

1. Optional Wi-Fi Antenna
2. Optional GPS Antenna
3. Optional WWAN Antenna
4. 2.5" SATA II HDD / SSD

Bottom

1. Docking connector

Ready for Use


After taking a quick look at your tablet computer, the following illustrations will get you ready for using it.

1. Mounting the Battery

- A. Mount the battery into the battery bay.



- B. Close the cover, turn clockwise and lock firmly with a flat-head screwdriver or a coin.



2. Connecting the AC Adapter



- A. Insert the DC Jack and firmly lock the connector clockwise.




- B. Plug the AC cord into the AC adapter.
C. Plug the AC power plug into an electrical outlet.

3. Turning ON the Power

- A. Make sure the battery is securely mounted. Connect all power cords properly.
- B. Turn on the power of your tablet computer by pressing the “**Power Button**”.



Press  to turn on the power of your tablet computer.

Note:

- *The power is able to turn ON without any battery mounted once all the power cords are connected.*

4. Turning Off the Power

Directly tap “Shut down” from your OS to turn OFF the power of your tablet computer. If your tablet computer stops responding, press and hold the power button for 4~5 seconds to “Force Shut down” your tablet computer.

Note:

- *Directly turning off the power of your tablet computer by “Force Shut down” will cause all unsaved data to be lost and is not recommended.*

Chapter2 - Operating Information

Start Using Your Tablet Computer

Always turn on your tablet computer by using the power button. This is the standard operating procedure to start using your tablet computer. After turning on the power of your tablet computer, it will start with the Operating System (OS) installed.

Boot Up

When you turn on the power, your computer will start to load the OS into the system memory. This start-up procedure is called “boot up”.

Power On Self-Test (POST)

Each time your computer is turned on, the BIOS will automatically perform a self-test of CPU, memory, hardware devices, and so on.

Stop Using Your Tablet Computer

Each time when you finish working with your tablet computer, there are several ways to stop your tablet computer from operating.

Shut down

Directly tap “Shut down” from your OS to turn OFF the power of your computer. Before shutting down, please do remember to save any unfinished works and close your applications to prevent your HDD/SSD from suffering possible data loss or damage. “Shut down” will turn OFF power of your computer. If you want to start your computer again, you need to turn it ON again by pressing the power button.

Sleep

Under “Sleep” mode, the system will temporarily save your work into the computer’s RAM. If you want to start your computer again, please press the power button to resume. You can enter this mode by directly tapping:

“Start” => “Shut down” => “Sleep” under Windows 7.

Hibernate

Under “Hibernate” mode, the system will save your work into HDD/SSD. If you want to start your tablet computer again, you need to press the power button. You can enter “Hibernate” mode by pressing the power button, or by directly tapping:

“Start” => “Shut down” => “Hibernate” under Windows 7.

Force Shut Down

In the event that your tablet computer hangs or stops responding, you can perform a force shut down by pressing and holding the power button for 4~5 seconds. Please note that any unsaved work or data will be lost this way.

Working with Power Button (Heater Kit)

Your tablet computer is equipped with a heater kit to enable work under low temperature. The heater will heat up the HDD to the temperature set by the user before booting the system. Also, the heater will constantly monitor HDD temperature. Once the temperature becomes lower, the heater will heat up again to maintain the temperature set by user.

Note:

- When ambient temperature is under +5 °C (the default setting for your tablet computer), the system may not boot up immediately. System will beep with HDD LED light flashing orange to indicate that the heater is in operation. The LED will blink faster as the HDD temperature approaches operational temperature. After 5~15 minutes, the system will boot up automatically.
- In emergency situations, you can skip the heating process by pressing and holding the power button for 9~11 seconds then release. The speaker will beep with a special sound to signify that the heating process has been skipped (Please note that not all devices are guaranteed to work properly in this case).
- Press the power button again during the heating process will shut down the computer.

The following is a list of functions associated with your tablet computer's power button:

1. Press and hold for 12 seconds, then release:
USB port is enabled and you can set a new value in Heater AP.
2. Press and hold for 9 ~ 11 seconds:
The system will skip heating process and force boot up.
3. Press and hold for 5 ~ 8 seconds:
Enable/Disable the sound of Heater.
4. Press and hold the power button for 4 seconds under OS:
Shut down the system.
5. Press the power button:
 - a. Power on the system.
 - b. Force Shut Down (If pressed while the heating process is underway).
 - c. Sleep/Hibernate (Dependent on OS settings).

Installing Operating System

Your computer is designed to operate with Microsoft Windows 7 or Windows 8 32 / 64-bit Operating System. Please connect your computer with an external USB-interface drive, such as an ODD or a USB thumb drive, and start the OS installation.







Note:

- *A USB hub may be required during installation to connect with an external USB-interface ODD, as the System USB port may not supply enough power. Please connect your USB hub with extra power supply to complete the installation.*

Using Indicators and Keyboard


Your tablet computer is designed with backlight buttons for easy and quick operations. Also, each LED indicator shows different meanings. The description of each LED indicator and button functions are provided for your operational reference.

LED Indicators

LED Indicator	Description
	Power Indicator: Green (Power); Flashing Red (S3: Sleep); Flashing Green (Battery power is lower than 10%)
	Charger Indicator: Orange
	HDD Indicator (Dual LED): Green (HDD); Orange (Heater)
	Wireless Devices Indicator: Blue
	Input Lock Indicator: Red
	Caps Lock Indicator: Green

Keyboard


1. US International (UI) keyboard layout:




2. British (GB) keyboard layout:




3. Swedish (SV) keyboard layout:



4. German (DE) keyboard layout:



5. Russian (RU) keyboard layout:



To perform 2nd layer combinational keystroke functions (keystroke functions printed in **blue**), press and hold the **[Fn]** key, and then press the corresponding key combinations.

A list of useful combinational button functions is provided below for operational reference:

Key	Description
[Fn] + [B]:	Switches your tablet computer's keyboard backlight on or off .
[Fn] + [↑]:	Increases Audio Volume.
[Fn] + [↓]:	Decrease Audio Volume.
[Fn] + [Del]:	Backspace Key.
[Fn] + [Tab]:	Escape Key.
[Fn] + [Q] ~ [S]:	Function Key F1 ~ F12 .

APP1~APP3 & Input Lock Hotkey

Key	Description
APP1	Increase brightness
APP2	Decrease brightness
APP3	LCD Backlight on/off
Input Lock	Input devices all off

Using Hard Disk Drive (HDD) / Solid State Drive (SSD)

Your tablet is equipped with 2.5" SATA II Hard Disk Drive (HDD) or Solid State Drive (SSD) for data storage. HDD/SSD is user removable, providing convenience and security. It can **ONLY** be removed while power is **OFF**.

Note:

- *Avoid dropping your HDD/SSD module. Do not expose it directly to high temperature, high humidity, and other hazardous environment. NEVER try to disassemble the module. Static discharge may destroy your device and data. Always pick up the module by touching the case only.*

Using ExpressCard

The computer supports 54mm and 34mm wide ExpressCard. You can install an ExpressCard while the computer is running. The computer automatically detects the card.


To install an ExpressCard:

- Hold the card with the top side of the card.
- Slide the card into the slot until the card is completely seated in its connector.

To remove an ExpressCard:

Press the card and remove the card gently.

The following illustration shows the insertion of ExpressCard 54mm:



Using SD Cards

Your tablet computer is equipped with a SD card slot. The SD card slot supports SDHC, SDXC, UHS-1. To avoid damages caused by misinsertion, please insert your SD card into the card slot properly with the connectors facing **down**, as shown below.



Intel® Rapid Start Technology

Your tablet computer can operate Intel® Rapid Start Technology when SSD is installed. This technology enables your system resume time not only to be as fast as wake-up time from S3 (Sleep) mode, but also to be more energy saving.

Before using Intel Rapid Storage Technology, please check the following system requirements:

System Requirement:

- Intel QM67 Express Chipset-based desktop board
- Intel Sandy Bridge i7-2610UE
- Solid State Drive (SSD)
- Operating system: Microsoft Windows 7/ 8 (32- or 64-bit edition)


Note:

- *Intel® Rapid Storage Technology Driver should be installed and can be found in Utility DVD.*
- *Please use “Intel® Rapid Start Technology User Guide” to setup the function. You can find the User Guide from Intel official website.*
- *Please remember to enable Rapid Start Technology from BIOS Advanced Menu.*
- *To cancel the Rapid Start Technology, please disable the function from BIOS Advanced Menu.*


Using the Touch Screen

Your tablet computer is equipped with a highly sensitive touch screen, allowing you to navigate on the touch screen easily without using other external devices. Before using the touch screen, please remember to install the driver first and then follow the instructions below to calibrate your stylus pen for a more precise positioning:

1. Tap “Configure” to start.



2. Use “Standard Calibration” and follow the instructions.



A stylus pen is provided for operating the touch screen. A list of operating tips is provided below to help you operate the touch screen more effectively with your stylus pen.

Desired Operation	Stylus Action
Single Click	Tap the touch screen once with your stylus pen.
Double Click	Quickly tap the touch screen twice with your stylus pen.
Drag and Drop	To drag, tap and hold the object gently with your stylus pen. Without moving your stylus pen away from the touch screen, move your stylus pen until you reach your destination. To drop, simply release your stylus pen from the touch screen.
Right Click	Press and hold your stylus pen on one point of the touch screen for 2~3 seconds. This is the same as using the right click of a mouse.

Note:

- *For adjusting display brightness, you can use APP1 to increase the display brightness and APP2 to decrease.*

Operating Wireless Devices

For your ease of operations, you can turn on/off your wireless devices through the proprietary software application - “**Device Power Manager**”.

Note:

- *Depending on the configuration of your tablet computer, your Device Power Manager menu may appear differently from the screenshots provided in this section.*
- *When you adjust User Account Control (UAC), a security feature in Windows, the setting value of Device Power Manager will be affected. So, once there is any adjustment on UAC, please uninstall Device Power Manager and reinstall it again.*

Bluetooth (Option)

The Bluetooth module provides your tablet computer with a short-range wireless communication protocol to connect with other compatible devices via the pre-installed embedded antenna. To activate your Bluetooth functions, please follow the instructions below.

1. Driver & Application Installation

- a. Install the Bluetooth driver first. Read from the Utility DVD and find the directory listed in the readme file to finish installation.
- b. Install the Device Power Manager application. Read from the Utility DVD and find the directory listed in the readme file to finish installation.

2. Launch the Device Power Manager

After launching the utility, please tap “Bluetooth” to enable the Bluetooth function (tap again to disable). Once the Bluetooth function starts up, the wireless LED indicator (color blue) will turn on and the Bluetooth icon will show up in the operating system accordingly.



Tap “Bluetooth” to enable the Bluetooth function (tap again to disable).

Once the Bluetooth function starts up, the wireless device LED indicator will turn on (color blue) and the Bluetooth icon will appear in the OS accordingly.

Wireless LAN (Option)

Wireless LAN is an optional wireless communication module for your tablet computer. An embedded antenna will be pre-installed in your tablet computer to access the internet wirelessly. To activate your Wireless LAN function, please follow the illustrations below:

1. Driver & Application Installation

- a. Install the Chipset Driver first. Read from the Utility DVD and find the directory listed in the readme file to finish installation.
- b. Then, install the Device Power Manager application. Read from the Utility DVD and find the directory listed in the readme file to finish installation.

2. Launch the Device Power Manager

After launching the utility, please tap “WLAN” for enabling the Wireless LAN function (tap again to disable).



Tap “WLAN” to enable the Wireless LAN function (tap again to disable).


Once the Wireless LAN function starts up, the wireless device LED indicator will turn on (color blue) and the Wireless LAN icon will appear in the OS accordingly.

Wireless Wide Area Network (Option)

Wireless Wide Area Network (WWAN) is an optional module for your tablet computer. With pre-installed embedded antenna and the optional WWAN module, your tablet computer will be able to engage in WWAN functions.

1. Insert the SIM card

- a. Turn OFF your tablet computer.
- b. Pull down the rubber lock cover.
- c. Insert the SIM card into the SIM card slot. To avoid damaging the SIM card slot, please make sure that the golden contact area on the SIM card is facing **upward** and the beveled corner is facing towards the tablet, as shown below.



- d. Firmly push the rubber lock cover back.

Note:

- *Before insert or remove SIM Card, please remember to turn OFF the tablet computer first.*
- *If you encounter difficulties in ejecting your SIM card, a coin of suitable size may be used in aiding the ejection of SIM card.*

2. Driver & Application Installation

- a. Please Install the WWAN driver first. For detailed instructions on installation procedures, please read from the Utility DVD and find the directory listed in the readme file. Follow the installation instructions to finish the driver installation.
- b. Install the Device Power Manager application. Read from the Utility DVD and find the directory listed in the readme file to finish installation.



Tap “WWAN” to enable the WWAN function (tap again to disable).

3. Launch the Device Power Manager

After launching the application, please tap “WWAN” for enabling the WWAN function (tap again to disable). Once the WWAN function starts up, the wireless device LED indicator will turn on (color blue).

4. Launch the AirCard Watcher

After installing appropriate drivers and applications, you can now access the WWAN AirCard Watcher and setup your WWAN connection parameters. The WWAN AirCard Watcher software can found from the Utility DVD. Follow the installation instructions to finish the software installation.


Screenshots of the WWAN AirCard Watcher are provided below for your reference. Please follow the procedure to set the connection.



1. Tap the Options first, and a User Options window will pop up.
2. Tap Firmware
3. Drop down the Network Operator list and choose an appropriate operator. If your operator is not on the list, please choose Generic UMTS.
4. Tap OK to complete the setting.

Once the WWAN function starts up, the wireless device LED indicator will turn on (color blue).

Note:

➤ You can find more setting information in Help Topics .

GPS (Option)

GPS is an optional module for your tablet computer. This GPS module supports both GPS and GLONASS systems. An embedded antenna is pre-installed in your tablet computer to support the functions of your GPS and GLONASS.

1. Driver & Application Installation

- a. Install the Device Power Manager application:

Read from the Utility DVD and find the directory listed in the readme file to finish installation.

- b. Install the GPS driver:

GPS (Driver): Read from the Utility DVD and find the directory listed in the readme file to finish installation.



Tap “GPS” to enable the GPS function (tap again to disable).

2. Navigation & Mapping Software Installation

Please install your 3rd party navigation and mapping software after installing your GPS driver. Refer to your navigation and mapping software manual for installation and procedures on application setup and access.

Once the GPS function starts up, the wireless device LED indicator will turn on (color blue).

Note:

- Wireless devices can be turned ON/OFF through BIOS. Once a device is turned off through BIOS, its button on the Device Power Manager will be colored in yellow and with a prohibition marker. For example, the following illustration shows that WLAN, WWAN and GPS devices are disabled through BIOS. To turn on, please enter into BIOS and enable the functions. For more information on BIOS setting, please refer to “RF Device Control Configuration Sub-Menu” section.



Using Invisible Mode (Option)

Invisible Mode is an optional function which can quickly turn off all light sources, including LCD backlight, LED indicators and keyboard backlight.

The Invisible Mode Switch is located at the upper right corner of the tablet computer, as the figure shows below. To turn on Invisible Mode, simply switch to the ON position, while to turn off it, switch to the OFF position.



Invisible Mode Switch:

- ON: Turn on the Invisible Mode
- OFF: Turn off the Invisible Mode

Using Docklight DL10 (Option)


Docklight acts as docking unit or port enhancer. It contains more ports that are not available on system unit.

Mount Docklight

1. Open the rubber cap on the docking connector.
2. Align the docking connector.
3. Attach Docklight.
4. Fix the screws.


Docklight ports

Top



1. Docking connector

Bottom and Left:



1. Audio jacks (Microphone/Speaker)
2. RGB DB15 port
3. Optional GLAN RJ45
4. Serial port (COM3: Default RS232)
5. USB2.0 port 1, 2 (standard type)
6. USB2.0 port 3, 4 (proprietary sealed type)
7. Serial port (COM2: Default RS232)
8. DC power jack
 - Default: 2-pin
 - Optional: Mil 3-pin

Chapter3- Managing Power

AC Adapter

The AC adapter performs two functions:

- It powers the computer from an external AC source.
- It charges the computer battery.

The adapter automatically detects the AC line voltage (110V or 220V) and adjusts accordingly.

The following are recommended when using the AC adapter:

- Use a properly grounded AC outlet.
- Use one AC outlet exclusively for the computer. Having other appliances on the same line may cause interference.
- Use a power strip with built-in surge protection.

Connect the AC adapter:

- Plug the AC cord to the adapter.
- Plug the other end of the AC cord into the wall outlet. Make sure the green LED on the adapter turns on.
- Attach the DC plug into the power jack of the computer; turn the lock ring clockwise to secure it.

AC Adapter Indicator

The green LED indicates that AC power is ready.

Battery

The computer will automatically switch to battery when the external power source (AC adapter or optional vehicle adapter) is disconnected.

Battery Power Saving Tips

The computer comes with an intelligent power-saving feature. You may extend the battery life by:

- Setup power saving functions in Operating System Power Management options (e.g. Windows Power Options).
- Lower the intensity of the display by brightness control.
- Turn the computer into standby (by Sleep or Power button) when it is temporarily not in use.
- Shut down the computer when it will not be in use for longer period of time.

Battery Low

When the battery is nearly exhausted, the computer gives the following “Battery Low” warnings:


- Windows battery low warning.
- The power LED flashes.

Once the “Battery Low” warning occurs, please:

- Save and close the files you are currently working on then shut down the computer.
- Plug in AC or vehicle adapter to recharge the battery.

Battery Gauge

You may check battery status from battery gauge. Click the power/battery icon to reveal the battery gauge window. The following is the illustration of Battery Gauge in Windows OS.



Note:

- *Battery characteristic varies depending on factors such as ambient temperature, charging method, load current, aging, etc. For example, the chemicals of the battery are more inactive at low temperature, thus decreases the output power.*
- *The battery gauge should only be used as a reference. Please do not expect it to show the exact amount of the power remaining. There is no memory effect on Lithium Ion battery cells. However, discharge the battery to nearly empty every month will help calibrating the internal gauge.*

Charging the Battery

Plug in the AC adapter or vehicle adapter to start the battery charging. If the battery is already full, the sense circuitry will stop high current charge within several minutes.

The LED Indicator turns ON when the battery is charging and turns OFF when the battery charge is completed.

To charge the Secondary Battery, simply install it into the computer and attach the AC adapter. The internal charger will first charge the Primary battery and then the Secondary one.

Optional Multi Battery Charger can charge Primary and Secondary batteries externally.

ACPI Support

Your computer supports ACPI (Advanced Configuration and Power Interface) for power management. With ACPI and an ACPI-compliant operating system (such as Microsoft Windows), this feature will allow you to reduce the power consumption and conserve energy. By supporting ACPI, the AC adapter LED and the Power indicator LED will show in different ways. The followings are detailed descriptions of LED indicators and their meanings:

Sleep:

Power LED indicator is blinking RED; other LED indicators are OFF

Hibernate:

All LED indicators are OFF

Shut down:

All LED indicators are OFF

USB Fast Charging

Your tablet supports USB fast charging feature, enabling to quickly charge your fast-charging compatible devices. But note, fast charging is not supported in every power mode. The following table shows details for USB Charging information:

Mode		USB 2.0 Charging Features
Power off	AC	Fast charging supports
	Battery	No charging
Power on	AC	Normal charging
	Battery	Normal charging
S3	AC	Fast charging supports
	Battery	Fast charging supports

Chapter 4 - BIOS Setup

Press **[F2]** at boot up to enter BIOS setup. Use arrow keys to select options and **[+/-]** to modify them. When finished, move to “**Exit**” and press **[Enter]** then confirm save by pressing **[Y]**.

Main Menu

Aptio Setup Utility			
Main	Advanced	Chipset	Boot
BIOS Information BIOS Vendor Core Version Compliance Project Version Build Date and Time EC Version			Choose the system default language
System Language [English] System Date [Wed 06/19/2013] System Time [16:19:20]			→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
Access Level Administrator			

Note:

- The contents may vary depending on computer configurations.
- Incorrect settings may cause system malfunction. To correct it, restore the Optimized Defaults with F3.

Main Menu Selections

You can make the following selections on the Main Menu. Use the sub-menus for other selections.

Feature	Options	Description
System Date	MM/DD/YYYY	Set the system date Month, Day, Year.
System Time	HH:MM:SS	Set the system time Hour, Minute, Second.

Advanced Menu

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
<ul style="list-style-type: none">▶ Trusted Computing▶ SATA Configuration▶ Intel (R) Rapid Start Technology▶ USB Configuration▶ IT8783F Super IO Configuration▶ RF Device Control▶ EC Thermal Control				Trusted Setting	Computing
				<p>→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit</p>	

Advanced Menu Selections

You can make the following selections on the Advanced Menu.

Feature	Options	Description
Trusted Computing	Disabled Enabled	TPM Support
SATA Configuration	SATA Mode Selection Serial ATA Port 0 Software Preserve	SATA Mode Selection: IDE, AHCI, RAID
Intel (R) Rapid Start Technology	Disabled Enabled	Enable or disable Intel (R) Rapid Start Technology.
USB Configuration	Disabled Enabled	Legacy USB Support USB3.0 Support XHCI Hand-off EHCI Hand-off
IT8783F Super IO Configuration	VBIOS Default CRT LFP CRT+LFP TV LFP-SDVO EFP TV-SDVO CRT+LFP-SDVO CRT+EFP	Select the Video Device that will be activated during POST
RF Device Control	Disabled Enabled	GSM, GPS, BLUETOOTH, WLAN
EC Thermal Control		Thermal cooling trip point

Trusted Computing Sub-Menu

Advanced		Aptio Setup Utility
Configuration TPM SUPPORT	[Disable]	Enables or Disables BIOS support for security device. O.S. will not show Security Device. TCG EFI protocol and INT1A interface will not be available. →←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
Current Status Information SUPPORT TURNED OFF		

SATA Configuration Sub-Menu

Advanced		Aptio Setup Utility
SATA Mode Selection	[AHCI]	Determine how SATA controller(s) operate.
Serial ATA Port 0	Empty	→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
Software Preserve	Unknown	
Serial ATA Port 1	Empty	
Software Preserve	Unknown	
Serial ATA Port 2	SATA SSD (120.0	
Software Preserve	SUPPORTED	

SATA Configuration Sub-Menu Selections

You can make the following selections on the SATA configuration sub-menu.

Feature	Options	Description
SATA Mode Selection	IDE AHCI RAID	-
Port 0	-	Enable or Disable SATA Port
Hot Plug	-	Designates this port as Hot Pluggable

Intel (R) Rapid Start Technology Sub-Menu

Aptio Setup Utility	
Advanced	
Intel (R) Rapid Start Technology [Disabled]	Enables or disable Intel (R) Rapid Start Technology
	→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

USB Configuration Sub-Menu

Advanced		Aptio Setup Utility
USB Configuration USB Devices: 1 point Legacy USB Support [Enabled] USB3.0 Support [Enabled] XHCI Hand-off [Enabled] EHCI Hand-off [Disabled]		Enables Legacy USB support. AUTO option disables legacy support if no USB devices are connected. Disable option will keep USB devices available only for EFI applications →←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

USB Configuration Sub-Menu Selections

You can make the following selections on the USB configuration sub-menu.

Feature	Options	Description
Legacy USB enabled	Disabled Enabled	Enables Legacy USB support. AUTO option disables legacy support if no USB devices are connected. DISABLE option will keep USB devices available only for EFI applications.
Usn3.0 Support	Disabled Enabled	Enable/Disable USB3.0 (XHCI) Controller support.
XHCI Hand-off	Disabled Enabled	This is a workaround for OSe without XHCI hand-off support. This XHCI ownership change should be claimed by XHCI driver.
EHCI Hand-off	Disabled Enabled	This is a workaround for OSe without EHCI hand-off support. This EHCI ownership change should be claimed by EHCI driver.

IT8783F Super IO Configuration Sub-Menu

Advanced Aptio Setup Utility	
IT8783F Super IO configuration IT8783F Super IO Chip IT8783F ► Serial Port 0 Configuration	Set Parameters of Serial Port 0 (COMA)
	→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

IT8783F Super IO Configuration Sub-Menu Selections

You can make the following selections on the IT8783F super IO configuration sub-menu.

Feature	Options	Description
Serial Port	Disabled Enabled	Enable or Disable Serial Port (COM)
Change Settings	Auto IO=3F8h; IRQ=4; IO=3F8h; IRQ=3,45,6,7,10,11,12; IO=2F8h; IRQ=3,45,6,7,10,11,12; IO=3E8h; IRQ=3,45,6,7,10,11,12; IO=2E8h; IRQ=3,45,6,7,10,11,12;	Select an optimal setting for Super IO device.
COM 1 Mode Setting	RS232 RS422 TTL 1 RS485	Change COM port Settings

RF Device Control Configuration Sub-Menu

Aptio Setup Utility		
Advanced		
RF Device Control		RF Device Control Setting
GSM STATUS	Present	
GSM	[Enabled]	
GPS STATUS	Present	
GPS	[Enabled]	
BT STATUS	Present	
BLUETOOTH	[Enabled]	
WLAN STATUS	Present	
WLAN	[Enabled]	
		→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

RF Device Control Configuration Sub-Menu Selections

You can make the following selections on the RF Security Control sub-menu.

Feature	Options	Description
Wireless LAN	Disabled	Wireless Lan Control
	Enabled	Enabled Wireless function
WWAN	Disabled	WWAN Control
	Enabled	Enabled WWAN function
GPS	Disabled	GPS Control
	Enabled	Enabled GPS function
BlueTooth	Disabled	BlueTooth Control
	Enabled	Enabled Blue Tooth function

EC Thermal Control Sub-Menu

Advanced		Aptio Setup Utility	
EC Thermal Control		EC Thermal Control Setting	
Thermal cooling trip point	[87 C]	→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Chipset Menu

Aptio Setup Utility		
Main	Advanced	Chipset
▶ System Agent (SA) Configuration ▶ PCH-IO Configuration		System Agent (SA) Parameters
		→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit

Chipset Menu Selections

You can make the following selections on the Chipset sub-menu.

Feature	Options	Description
System Agent (SA) Configuration	-	System Agent (SA) Parameters
PCH-IO Configuration	-	PCH Parameter

PCH-IO Configuration Sub-Menu

Aptio Setup Utility		
Chipset		
Intel PCH RC Version	1.2.2.0	Enable or disable onboard NIC.
Intel PCH SKU Name	QM67	
Intel PCH Rev ID	05/B3	
PCH LAN Controller	[Enabled]	→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit
Wake on LAN	[Enabled]	
▶ USB Configuration ▶ PCI Express Configuration		

PCH-IO Configuration Sub-Menu Selections

You can make the following selections on the PCH-IO Configuration sub-menu.

Feature	Options	Description
PCH LAN Controller	Disabled Enabled	Enable or disable onboard NIC.
Wake on LAN	Disabled Enabled	Enable or disable integrated LAN to wake the system
USB Configuration	Disabled Enabled	USB Configuration settings
PCI Express Configuration	Disabled Enabled	PCI Express Configuration settings

Boot Menu

Aptio Setup Utility	
Main	Advanced
Chipset	Boot
Security	Save & Exit
Boot Option Priorities Boot Option #1 [P2: SATA SSD...] Boot Option #2 [IBA GE Slot 00C8 v...] Network Device BBS Priorities Hard Driver BBS Priorities	
Sets the system boot order →←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

The system will try to boot from device on top then the 2nd and so on. If there is more than one device in each category, only the device on top of sub-menu can boot up.

Boot Menu Selections

You can make the following selections on the Boot menu.

Feature	Options	Description
Boot Option #1	-	Sets the system boot order
Boot Option #2	-	Sets the system boot order
Network Device BBS Priorities	-	Set the order of the legacy devices in this group
Hard Drive BBS Priorities	-	Set the order of the legacy devices in this group

Security Menu

Aptio Setup Utility	
Main	Advanced
Chipset	Boot
Security	Save & Exit
Password Description If ONLY the Administrator's password is set, then this only limits access to Setup and is only asked for when entering Setup. If ONLY the User's password is set, then this is a power on password and must be entered to boot or enter Setup. In Setup the User will have Administrator rights. The password length must be in the following range; Minimum length 3 Maximum length 20 Administrator Password User Password HDD Security Configuration: HDD 0: SATA SSD	
Set Administrator Password →←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Security Menu Selections

You can make the following selections on the Security Menu.

Feature	Options	Description
Administrator Password	Enter Password New Confirm Password New	Controls detection of Processor Serial No. System must be reset or restarted from power-on for settings to take effect.
User password	Enter Password New Confirm Password New	Supervisor Password controls access to the setup utility.
HDD 0: SATA SSD	Enter Password New Confirm Password New	User Password controls access to the system at boot.

Save & Exit Menu

Aptio Setup Utility	
Main	Advanced
Chipset	Boot
Security	Save & Exit
Save Changes and Exit Discard Changes and Exit Save Changes and Reset Discard Changes and Reset	
Save Options Save Changes Discard Changes Restore Defaults Save as User Defaults Restore User Defaults Boot Override P2: SATA SSD IBA GE Slot 00C8 v1365 Realtek PXE B01 D00	
Exit system setup after saving the changes	
→←: Select Screen ↑↓: Select Item Enter: Select -/+ : Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	

Chapter 5 – Drivers and Applications

The Utility DVD includes all the drivers for the installed devices in your tablet computer. Please consult the dealer if there is any driver missing. Also, through Device Manager in Windows, you are able to perform “Driver Update” or check if there are still drivers for the devices needed to be installed. Please check the readme file on Utility DVD to get the latest information before installing device drivers.

Note:

- *Please install the chipset driver first.*
- *If the system requests for reboot after installing drivers, please reboot your tablet computer first before installing other drivers.*

Chipset

Windows 7/Ultimate 64-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Intel_Chipset", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_Chipset", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "infinst_autol.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Intel_Chipset", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "infinst_autol.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Intel_Chipset", and then follow the instructions to install.

VGA

Windows 7/Ultimate 64-bit:

Run "win64_15288.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Intel_VGA", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "win64_15288.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_VGA", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "win64_152812.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Intel_VGA\\64bit", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "win32_152812.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Intel_VGA", and then follow the instructions to install.

Audio

Windows 7/Ultimate 64-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Audio\\6777_PG360_Win8_Win7_Vista_XP", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Audio\\6777_PG360_Win8_Win7_Vista_XP", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Audio\\6777_PG360_Win8_Win7_Vista_XP", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "Setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Audio\\6777_PG360_Win8_Win7_Vista_XP", and then follow the instructions to install.

Intel ME

Windows 7/Ultimate 64-bit:

Run "Setup.exe" in the directory of " \Drivers\Windows 7 (64-bit)\Intel_ME\ME_SW_7.1.85.1216", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "Setup.exe" in the directory of "\Drivers\Windows 7 (32-bit)\Intel_ME\ME_SW_7.1.85.1216", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "Setup.exe" in the directory of " \Drivers\Windows 8 (64-bit)\Intel_ME\ME_SW_7.1.85.1216", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "Setup.exe" in the directory of " \Drivers\Windows 8 (32-bit)\Intel_ME\ME_SW_7.1.85.1216", and then follow the instructions to install.

Intel Rapid Storage Technology

Windows 7/Ultimate 64-bit:

Run "iata_cd_10.8.0.1003.exe" in the directory of "Drivers\Windows 7 (64-bit)\IntelR Rapid Storage Technology", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "iata_cd_10.8.0.1003.exe" in the directory of "Drivers\Windows 7 (32-bit)\IntelR Rapid Storage Technology", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "iata_cd.exe" in the directory of "Drivers\Windows 8 (64-bit)\IntelR Rapid Storage Technology", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "iata_cd.exe" in the directory of "Drivers\Windows 8 (32-bit)\IntelR Rapid Storage Technology", and then follow the instructions to install.

Wireless Power Manager

Windows 7/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Utilities\\0107\\", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Utilities\\0107\\", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Utilities\\0620\\", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Utilities\\0620\\", and then follow the instructions to install.

Touch Screen

Windows 7/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Touch Screen\\PenMount Windows Universal Driver V2.4.2.325(WHQL)", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Touch Screen\\PenMount Windows Universal Driver V2.4.2.325(WHQL)", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Touch Screen\\PenMount Windows Universal Driver V2.4.2.325(WHQL)", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Touch Screen\\PenMount Windows Universal Driver V2.4.2.325(WHQL)", and then follow the instructions to install.

USB3.0

Windows 7/Ultimate 64-bit:

Run "Texas Instruments xHCI Driver v1.12.25 (Multilanguaje - WHQL).exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\USB3.0\\Texas Instruments xHCI Driver v1.12.25 (Multilanguaje - WHQL)", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "Texas Instruments xHCI Driver v1.12.25 (Multilanguaje - WHQL).exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\USB3.0\\Texas Instruments xHCI Driver v1.12.25 (Multilanguaje - WHQL)", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "Texas_Instruments_xHCI_Driver_v1.16.2.0_WHQL_(Multilanguage).exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\USB3.0\\Texas_Instruments_xHCI_Driver_v1.16.2.0_WHQL_(Multilanguage)", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "Texas_Instruments_xHCI_Driver_v1.16.2.0_WHQL_(Multilanguage).exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\USB3.0\\Texas_Instruments_xHCI_Driver_v1.16.2.0_WHQL_(Multilanguage)", and then follow the instructions to install.

Ricoh SD Controller

Windows 7/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Ricoh\\Ricoh_Media_Driver_v2.13.16.01", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Ricoh\\Ricoh_Media_Driver_v2.13.16.01", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Ricoh\\Ricoh_Media_Driver_v2.24.12.11", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Ricoh\\Ricoh_Media_Driver_v2.24.12.11", and then follow the instructions to install.

Turbo Boost Monitor

Windows 7/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\IntelR Turbo Boost Technology Monitor", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\IntelR Turbo Boost Technology Monitor", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\IntelR Turbo Boost Technology Monitor", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\IntelR Turbo Boost Technology Monitor", and then follow the instructions to install.

Gigabit LAN

Windows 7/Ultimate 64-bit:

Run "PROWinx64.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Intel_82579LM", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "PROWinx32.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_82579LM", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "PROWinx64.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Intel_82579", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "PROWinx32.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Intel_82579", and then follow the instructions to install.

2nd Gigabit LAN (Option)

Windows 7/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\RTL8111E\\Install_Win7_7046_07202011", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\RTL8111E\\Install_Win7_7046_07202011", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\RTL8111E\\Install_Win7_7046_07202011", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\RTL8111E\\Install_Win7_7046_07202011", and then follow the instructions to install.

WiFi (Option)

Windows 7/Ultimate 64-bit:

Run "Wireless_15.3.1_Ds64.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Intel_WiFi6235\\WLAN\\64bit", and then follow the instructions to install.

*: Then into the "Wireless Power Manager" to turn on the WLAN device.

Windows 7/Ultimate 32-bit:

Run "Wireless_15.3.1_Ds32.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_WiFi6235\\WLAN\\32bit", and then follow the instructions to install.

*: Then into the "Wireless Power Manager" to turn on the WLAN device.

Windows 8/Ultimate 64-bit:

Run "Wireless_15.6_De64.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Intel_WiFi6235\\WLAN\\64bit", and then follow the instructions to install.

*: Then into the "Wireless Power Manager" to turn on the WLAN device.

Windows 8/Ultimate 32-bit:

Run "Wireless_15.6_De32.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\Intel_WiFi6235\\WLAN\\", and then follow the instructions to install.

*: Then into the "Wireless Power Manager" to turn on the WLAN device.

Bluetooth (Option)

Windows 7/Ultimate 64-bit:

*: First into the "Wireless Power Manager" to turn on the Bluetooth device.

Run "BT_2.2_s64.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\Intel_WiFi6235\\BT\\64bit", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the Bluetooth device.

Run "BT_2.2_s32.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_WiFi6235\\BT\\32bit", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

*: First into the "Wireless Power Manager" to turn on the Bluetooth device.

Run "BT_2.6.1211_e64.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\Intel_WiFi6235\\BT\\64bit", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the Bluetooth device.

Run "BT_2.6.1211_e32.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\Intel_WiFi6235\\BT\\", and then follow the instructions to install.

GPS (Option)

Windows 7/Ultimate 64-bit:

GPS(u-blox):

*: First into the "Wireless Power Manager" to turn on the GPS device.

Run "ubloxGnss_sensor_windows_3264_v2.1.0.5.exe" in the directory of "`\Drivers\Windows 7 (64-bit)\GPS(u-blox)`", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the GPS device.

Run "ubloxGnss_sensor_windows_3264_v2.1.0.5.exe" in the directory of "`\Drivers\Windows 7 (32-bit)\GPS(u-blox)`", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

*: First into the "Wireless Power Manager" to turn on the GPS device.

Run "ubloxGnss_sensor_windows_3264_v2.1.0.5.exe" in the directory of "`\Drivers\Windows 8 (64-bit)\GPS(u-blox)`", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the GPS device.

Run "ubloxGnss_sensor_windows_3264_v2.1.0.5.exe" in the directory of "`\Drivers\Windows 8 (32-bit)\GPS(u-blox)`", and then follow the instructions to install.

WWAN (Option)

Windows 7/Ultimate 64-bit:

*: First into the "Wireless Power Manager" to turn on the WWAN device.

Install Driver:

Run "SWIGobi3kSetup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\AirPrime MC8305 HSPA module (Gobi)\\GenericGobi3k", and then follow the instructions to install.

Install MC8305 module AP:

Run "Watcher_Generic_Q.msi" in the directory of "\\Drivers\\Windows 7 (64-bit)\\AirPrime MC8305 HSPA module (Gobi)\\", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the WWAN device.

Inteall Driver:

Run "SWIGobi3kSetup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\AirPrime MC8305 HSPA module (Gobi)\\GenericGobi3k", and then follow the instructions to install.

Install MC8305 module AP:

Run "Watcher_Generic_Q.msi" in the directory of "\\Drivers\\Windows 7 (32-bit)\\AirPrime MC8305 HSPA module (Gobi)\\", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

*: First into the "Wireless Power Manager" to turn on the WWAN device.

Install Driver:

Run "SWIQMIGobi3kSetup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\AirPrime MC8305 HSPA module (Gobi)\\GenericGobi3k", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

*: First into the "Wireless Power Manager" to turn on the WWAN device.

Inteall Driver:

Run "SWIQMIGobi3kSetup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\AirPrime MC8305 HSPA module (Gobi)\\GenericGobi3k", and then follow the instructions to install.

TPM (Option)

Windows 7/Ultimate 64-bit:

*: First into the "BIOS" to turn on the TPM device.

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (64-bit)\\TPM", and then follow the instructions to install.

Windows 7/Ultimate 32-bit:

*: First into the "BIOS" to turn on the TPM device.

Run "setup.exe" in the directory of "\\Drivers\\Windows 7 (32-bit)\\TPM", and then follow the instructions to install.

Windows 8/Ultimate 64-bit:

*: First into the "BIOS" to turn on the TPM device.

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (64-bit)\\TPM", and then follow the instructions to install.

Windows 8/Ultimate 32-bit:

*: First into the "BIOS" to turn on the TPM device.

Run "setup.exe" in the directory of "\\Drivers\\Windows 8 (32-bit)\\TPM", and then follow the instructions to install.

Chapter 6 – Specifications

Platform

Intel® Huron River Platform

CPU

Intel® Sandy Bridge i7-2610UE

- 4 MB Intel Smart Cache Memory

PCH

Intel® Cougar Point QM67

Memory

Max. 8GB System Memory

- Industrial grade
- DDR3 SO-DIMM x 1, 1333MHz

Touch Screen

Type: 9" WXGA with LED B/L

Resolution: 1280 x 768 pixels

Brightness (min.~ typ.): 530~700 nits (min.~typ.)

Single touch resistive type

Polarized, Anti-Glare and Anti-Reflective

Optional Invisible mode on/off

Hard Disk Drive (HDD)/ Solid State Drive (SSD)

Type: 2.5"

Interface: SATA II

Keyboard

- USB interface
- QWERTY keyboard with backlight


Audio

HD Audio and Stereo Speakers

I/O Ports

- Serial port DB9 (Default RS232)
- GLAN RJ45
- Multi Bay:
 - ExpressCard slot (ExpressCard/54) x 1(Top)
 - SIM Card slot x 1 + SD Card slot x 1(Bottom)
- Docking connector x 1
- USB 2.0 ports :
 - USB 2.0 port x 1 (Top)
 - USB 2.0 with Fast Charger port x1 (Bottom)
- DC power jack

Note:

- *WOR (Wake On Ring) is provided only on COM1.*
- *The bottom USB port supports Fast Charging, where the icon on rubber cap has a lightening mark: .*
- *SIM Card slot function requires optional WWAN module installed in your tablet computer.*
- *Limitation: USB2.0 is internal waterproof, but the USB isolate compartment is NOT waterproof.*
- *The max. baud rate for COM port supports to 115,200 bps.*

Dimensions and Weight

- Dimensions (mm):
250 x 190 x 39 mm (without Bumper)
259 x 199 x 49.2 mm (with Bumper)
- Weight: 1.9Kg (4.18 lb)

Note:

- *Weight shown above includes HDD, RF modules, but without battery. Weight varies depending on system configurations.*

Power

Primary Battery:

Type:	6 x 18650 cells Lithium Ion (BDA3A)
Capacity:	10.8V/ 5800mAh
Dimensions:	149 mm (W) x 57.4 mm (D) x 20.5 mm (H)
Weight:	300 g (0.65 lb.)

Optional 2nd Battery:

Type:	9 x 18650 cells Lithium Ion (BD83B)
Capacity:	11.1V/ 7200mAh
Dimensions:	150 mm (W) x 90 mm (D) x 20 mm (H)
Weight:	500 g (1.1 lb.)

AC Adapter

Input Voltage:	AC 100 - 240V
Frequency:	50/60 Hz
Output Voltage:	DC 19V
Maximum Power:	90 Watts
Dimensions:	133 mm (W) x 58mm (D) x 30mm (H)
Weight:	400 g (0.88 lb.)

DC-In:

12~32V with Surge Protector

- I-model: Industry 2 pin DC-in Connector
- M-model: Military 3 pin DC-in Connector

Environmental, Safety & EMC

CE, FCC, RoHS2.0, WEEE, REACH, IP54, MIL-STD-810G, MIL-STD-461F

Operating & Storage Temperature

Operating Temp.: I: 0°C~+40°C

M: -20°C~+50°C

Optional: -30°C~+50°C

Storage Temp.: -40°C ~ +70°C

Materials and Recycling

Materials of the computer are as follows:

Cabinet:	Magnesium alloy AZ91D UL grade PC+ABS GE C2800 or TN-3813BW
Bracket:	Aluminum 5052 Steel with Nickel plating Stainless Steel S304
PCB:	FR-4, UL 94V0
Battery:	Rechargeable Lithium Ion cells
Packing:	Carton: Unbleached paper Cushion: Recyclable PE Carrying bag: Recyclable PE Fiber Quick Guide: Paper

Please recycle the parts according to local regulations.

Chapter 7 – Optional Devices

Communication

- WiFi/Bluetooth:
 - Intel® Centrino® Advanced-N 6235, Dual Band
 - Board Form Factor: PCIe Half Mini Card
 - Wi-Fi Certified: 802.11 a/b/g/n
 - Bluetooth: Supports BT 2.1, 2.1+EDR, 3.0, 3.0+HS, 4.0 (BLE)
 - Interface: PCIe (WiFi)/USB (BT)
- WWAN: Gobi 3000 (USB interface, Mini PCIe form factor)
- GPS: u-blox Neo-M8N (USB interface)
- 2nd Gigabit LAN for DL10: 1Gbps (internal Mini PCIe Card)

Memory Card

The memory card can expand main memory to facilitate better system performance. The cards are available as following: 4/8GB DDR3 DRAM 1333MHz (Max. total memory 8 GB).

2nd Battery

A Lithium Ion rechargeable 2nd battery may mount on the rear. It has about 1.5 times capacity of primary battery and same Smart Battery compliance.

The computer's internal charger can detect 2nd battery and perform charging accordingly.

Security

TPM (Trusted Platform Module) version 1.2 (on up board)

Note:

- *TPM supports operating temperature: -20°C ~50°C.*

Docklight DL10

The Docklight can attach to computer for mobile or stationary operation.

Ports:	Serial x 2, USB2.0 x 4, RGB, Audio (speaker out, microphone in), DC jack, Optional Giga LAN RJ45 x 1
Dimensions:	250mm (W) x 37mm (D) x 61mm (H)
Weight:	0.45Kg (1 lb.) approximately
DC input:	12~32V
Environmental & Certifications:	CE, FCC, IP54

Note:

- *Serial ports: COM2/COM3 default RS232*
- *USB Ports: 2 standard and 2 proprietary environmentally sealed USB jacks.*
- *Audio port: 3.5 mm Jack*
- *Optional Giga LAN requires 2nd Giga LAN card installed.*

Multi-Battery Charger DR

The charger provides two slots for the Primary and Secondary battery respectively. It allows charging of both batteries simultaneously and accepts power from AC adapter or Vehicle adapter. It takes approximately 3~4 hours to fully charge both batteries.



External USB Keyboard

An optional 89-key external USB keyboard with LED backlight and IP rating of IP54 is available for your tablet computer. The detailed specification is provided below:

- 89-key layout emulates 101/102-key KB
- Life: >1 million times, water/dust protection up to IP54
- Back-light illumination (backlight device: green LED)
- PS/2 compatible Trackpoint and mouse buttons
- Dimensions: 323.4 mm (W) x 172 mm (D) x 25 mm (H)
- Weight: 1.1 kg



Track point

The track point is functionally equivalent to a mouse. Pushing the track point may move the cursor on the screen. The 2 buttons act same as mouse buttons.

Backlight

Press **[I-O]** key for approximately 1 second turns keyboard backlight ON or OFF.

Mini Keyboard KBD

Mini Keyboard KBD is designed for all models. KBD also brings convenience of use through multi-language keyboard versions and USB interface. The detailed specification is provided below:

- USB interface with 30 cm USB cable
- 66-Key design with function keys to simulate standard keyboards.
- StickPointer to simulate mouse and keypad
- Currently support versions:
English (UI), English (UK), German (DE), Swedish (SV) and Russian (RU) 5 versions.
- LED Backlight
- Caps Lock, Number Lock, Scroll Lock, and Smart Card Reader LED Indicators
- Magnesium Alloy Case (Black)
- Operating Temperature: -20 ~ 50°C (-4 ~ 122°F)
- Storage Temperature: -40 ~ 70°C (-40 ~ 158°F)
- Optional Built-in Smart Card Reader
- Dimensions: 190 mm (W) x 90 mm (D) x 12 mm (H)
- Weight: 170 g
- IP55



Chapter 8 – Maintenance and Service

Cleaning

ALWAYS turn OFF the power, unplug the power cord and remove the battery before cleaning.

The exterior of the system and display may be wiped with a clean, soft, and lint-free cloth. If there is difficulty removing dirt, apply non-ammonia, non-alcohol based glass cleaner to the cloth and wipe.

An air gun is recommended for cleaning water and dust. For salty water please clean with fresh water then blow-dry with an air gun.

Troubleshooting

Should the tablet computer fail to function properly, the troubleshooting steps below may be followed.

- Power Problems:

When I turn on the Tablet computer, it does not respond.

- If you are using battery power, check if the battery is charged
- If you are using AC power, ensure that the connection of AC adapter is correct.

I cannot return from Hibernation while on battery power

- The battery might be drained. Please plug the tablet into AC power.
- Hard reset the device by pressing the power button for 4 seconds

Unexpected or improper shutdown causes BIOS to reset to Optimized Default

- This could be a power problem. Please connect the AC power adapter to fix the abnormal shutdown problem.
- Minimize the configuration, i.e. remove extra peripherals and devices.
- Remove the modules one by one (HDD, Battery, etc.).
- Remove the software suspected.
- Set BIOS fail-safe default.
- Re-install operating system and application software.

RMA Service

If troubleshooting solutions are unsuccessful, consult your dealer for RMA.

Shipping instructions:

1. Remove any personal add-on devices or other media.
2. Use the original shipping container and packing materials, if possible.
3. If the original packing materials are not available, wrap the equipment with soft material (e.g. PU/PE form) then put the wrapped equipment into a hard cardboard shipping box.
4. Include a sheet with the following information: (Note: Please keep a copy of this sheet for your records.)
 - Name
 - Address
 - Unit serial number
 - Place and date of purchase or the original invoice number
 - Date of failure
 - A DETAILED description of the problems you have encountered including: The operating system, the add-on device installed (if any), the application software, the failure phenomenon, etc.
 - A list of the hardware/software configuration, if applicable.
5. Clearly mark the outside of the shipping box with the RMA #. If an RMA # is not present on the shipping box, receiving will be unable to identify it and it might be returned.
6. Unless prior arrangements have been made, the customer is responsible for all shipping costs. Unauthorized use of the company's shipping accounts is not permitted.

